

## BARRIER MATERIALS INFORMATION

*CONFIDENTIAL BUSINESS INFORMATION*

<b>COMPANY</b>	
Address	VersaFlex Inc. 87 Shawnee Ave. Kansas City, KS 66105
Contact	Jamie House
Phone Number	(913) 321-9000
<b>PRODUCT DESCRIPTION</b>	
	Polyurea Interior/Lining barrier system for tanks, vessels, storage containers, and pipes that are used for potable/drinking water.
Product Brand Name/Model Number	Aqua Vers AV20
<b><u>MATERIAL CHARACTERISTIC</u></b>	<b><u>DESCRIPTION</u></b>
	The Aqua Vers AV20 is a urethane primer used as a penetrating sealer.
Minimum Tank Size	10,000 Gal
Maximum Surface Area/Volume Ratio (sq cm/L)	16.8
Colors	N/A
Number of Coats	See Comment Below
Dry film thickness (mils)	See Comment Below
Recoat Dry Time/Temperature	N/A
Total Cure Time/Temperature	45 Minutes maximum at Ambient Temp.
Mix Ratio	See Comment Below
Flushing or preparation instructions prior to use	Please refer to manufacturer's instruction or call technical service at (913) 321-9000
Other Comments	If an additional information should be needed such as MSDS or TDS sheets, please refer to technical Services (888) 649-7713
<b>WATER CONTACT SIZE RESTRICTION</b>	<b>CONTACT TEMP – Ambient</b>
	<b>CONTACT MATERIAL</b>

*REVISED: 2/26/10*