

BARRIER MATERIALS INFORMATION

CONFIDENTIAL BUSINESS INFORMATION

COMPANY	
Address	VersaFlex Inc. 87 Shawnee Ave. Kansas City, KS 66105
Contact	Jamie House
Phone Number	(913) 321-9000
PRODUCT DESCRIPTION	
	Polyurea Interior/Lining barrier system for tanks, vessels, storage containers, and pipes that are used for potable/drinking water.
Product Brand Name/Model Number	Aqua Vers 201
<u>MATERIAL CHARACTERISTIC</u>	<u>DESCRIPTION</u>
	The Aqua Vers 201 is a 2k Polyaspartic Ester Polyurea topcoat.
Minimum Tank Size	10,000 Gal
Maximum Surface Area/Volume Ratio (sq cm/L)	16.8
Colors	N/A
Number of Coats	See Comment Below
Dry film thickness (mils)	See Comment Below
Recoat Dry Time/Temperature	N/A
Total Cure Time/Temperature	15 Minutes minimum at Ambient Temp.
Mix Ratio	(A:B) – (1:1)
Flushing or preparation instructions prior to use	Please refer to manufacturer's instruction or call technical service at (913) 321-9000
Other Comments	If an additional information should be needed such as MSDS or TDS sheets, please refer to technical Services (888) 649-7713
WATER CONTACT SIZE RESTRICTION	CONTACT TEMP – Ambient
	CONTACT MATERIAL

REVISED: 2/26/10