



Certified Product Listing

For:

Drinking Water System Components – Health Effects

Company:

Rhino Linings Corporation
9747 Businesspark Ave
San Diego, CA 92131, United States

Plant Location:

Greenville, TX, United States

Standards:

NSF/ANSI/CAN 61 - 2022

Certificate:

Issued Date: 02/18/2019

Material/Product:

Chemical Resistant Elastomeric Coating

Contact Temperature:

23 ± 2°C

Models:

HI-Chem 11-70 Isocyanate / Resin



Product certified to NSF/ANSI/CAN 372 conforms to the requirements for "Lead Free" plumbing products as defined by California, Vermont, Maryland and Louisiana state laws and by section 1417 of the US SDWA.



Material Characteristics:

Minimum pipe diameter (inches): 0.75 in.

Maximum pipe surface area/volume ratio (sq in/L): 326 (2103.22 sq cm/L)

Minimum tank size (gallons): 5 gal

Maximum tank surface area/volume ratio (sq in/L): 40.4 (260.64 sq cm/L)

Maximum dry film thickness per coat (mils): 120 Mils

Number of coats: 4-5

Is additional coating required (e.g. top coat, primer, intermediate coat)? (Y/N): Refer to manufacturer instructions for details

Total cure time and temperature: 24 hr @ 23Â°C

Shortest cure time between coats or layers: 4 seconds @ 23Â°C

Mix ratio: 1:1

Colors: Limited color range available

Is this paint/coating system intended to be applied to a pipe? (Y/N): Yes

(1) Certified for use on a new pipe? (Y/N): Yes

(2) Certified for use on a pipe intended for immediate return to service? (Y/N): Yes



Product certified to NSF/ANSI/CAN 372 conforms to the requirements for "Lead Free" plumbing products as defined by California, Vermont, Maryland and Louisiana state laws and by section 1417 of the US SDWA.