

ALS Group USA, Corp.

10450 Stancliff Rd. Suite 210 Houston, Texas 77099

Certified Product Listing

For:

Drinking Water System Components - Health Effects

Company:

Zurn Water, LLC - Wilkins 1747 Commerce Way Paso Robles, CA 93446, United States

Plant Location:

Paso Robles, CA, United States

Standards:

NSF/ANSI/CAN 61 - 2022 NSF/ANSI 372 - 2022

Certificate:

Issued Date: 06/10/2016

Material/Product:

Water Pressure Reducing Valve (500XL)

Contact Temperature:

23 ± 2°C

Models:

500XL (Size 1/2" - 3")

OPTIONS: (Any combination of options may be used)

None â€" Single union FNPT tailpiece connection (1/2" â€" 2" only)

None â€" Integral FNPT X FNPT connection (2-1/2" â€" 3" only)

C â€" Single union FC (female copper sweat) tailpiece connection

CPVC â€" Single union female CPVC tailpiece connection (3/4" & 1" only)

HLR â€" High/Low range spring - 10 to 125 psi spring range, factory set at 50 psi

HR â€" High range spring - 75 to 125 psi spring range, factory set at 85 psi

HT – 180 °F max temperature

L â€" Model does not contain an integral by-pass check valve (3/4" â€" 2" only)

LPC â€" 140 °F max temperature and 10 to 35 psi spring range, factory set at 20 psi

LPV \hat{a} €" 180 °F max temperature and 10 to 35 psi spring range, factory set at 20 psi

SC $\hat{a} {\in} \text{``}$ Sealed cage bell housing with stainless steel adjustment bolt and lock nut

P – Cap tapped and plugged for gauge

YSBR â€" Model SXL lead-free bronze "Y" strainer attached on inlet (1/2" â€" 2" only)

FC â€" Body with flanged end connections (2" â€" 3" only)



