



## Certified Product Listing

**For:**

Drinking Water System Components - Health Effects

**Company:**

Zurn Wilkins  
1747 Commerce Way  
Paso Robles, CA 93446, United States

**Plant Location:**

Paso Robles, CA, United States

**Standards:**

NSF/ANSI/CAN 61 - 2020  
NSF/ANSI/CAN 372 - 2020

**Certificate:**

Issued Date: 10/29/2019

**Material/Product:**

Water Pressure Reducing Valve (600XL, 625XL)

**Contact Temperature:**

23 ± 2°C

**Models:**

600XL (Size 1/2" - 2")  
625XL (Size 3/4" - 1")

OPTIONS: (Any combination of options may be used)

None - Single union FNPT tailpiece connection

C - Single union FC (female copper sweat) tailpiece connection

CPVC - Single union female CPVC tailpiece connection (3/4" & 1" only)

HLR - High/Low range spring - 10 to 125 psi spring range, factory set at 50 psi

HR - High range spring - 75 to 125 psi spring range, factory set at 85 psi

HT - 180 °F max temperature

L - Model does not contain an integral by-pass check valve (3/4" - 2" only)

LPC - 140 °F max temperature and 10 to 35 psi spring range, factory set at 20 psi

LPV - 180 °F max temperature and 10 to 35 psi spring range, factory set at 20 psi

SC - Sealed cage bell housing with stainless steel adjustment bolt and lock nut

P - Cap tapped and plugged for gauge



Product certified to NSF/ANSI/CAN 372 conforms to the requirements for "Lead Free" plumbing products as defined by California, Vermont, Maryland and Louisiana state laws and by section 1417 of the US SDWA.