



Certified Product Listing

For:

Drinking Water System Components - Health Effects

Company:

Zurn Wilkins
1747 Commerce Way
Paso Robles, CA 93446, United States

Plant Location:

Paso Robles, CA, United States

Standards:

NSF/ANSI/CAN 61 - 2020
NSF/ANSI/CAN 372 - 2020

Certificate:

Issued Date: 10/14/2019

Material/Product:

Water Pressure Reducing Valve (NR3XL)

Contact Temperature:

23 ± 2°C

Models:

NR3XL (Size 1/2" - 2")

OPTIONS: (Any combination of options may be used)

None - Single union FNPT tailpiece connection

C - Single union FC (female copper sweat) tailpiece connection

CPVC - Single union female CPVC tailpiece connection (3/4" & 1" only)

PEX - Single union PEX tailpiece connection (3/4" & 1" only)

DU - Double union FNPT tailpiece connection (or used with C, CPVC, PEX)

DULU - Regular body less union (no tailpieces), integral FNPT X FNPT

DM - Double male meter thread connection (no tailpieces) (3/4" & 1" only)

DMSS - DM with SS spring & seal cage (3/4" & 1" only)

P - Body tapped and plugged for gauge

SC - Sealed cage bell housing with stainless steel adjustment bolt, lock nut, and spring

HRSC - High range spring with SC (1/2" - 1-1/4" only)



Product certified to NSF/ANSI/CAN 372 conforms to the requirements for "Lead Free" plumbing products as defined by California, Vermont, Maryland and Louisiana state laws and by section 1417 of the US SDWA.