



## Certified Product Listing

**For:**

Drinking Water System Components - Health Effects

**Company:**

Zurn Wilkins  
1747 Commerce Way  
Paso Robles, CA 93446, United States

**Plant Location:**

Paso Robles, CA, United States

**Standards:**

NSF/ANSI/CAN 61 - 2020  
NSF/ANSI/CAN 372 - 2020

**Certificate:**

Issued Date: 07/07/2020

**Material/Product:**

Reduced Pressure Principle Backflow Preventer (375, 475)  
Double Check Valve Backflow Preventer (350, 450)

**Contact Temperature:**

23 ± 2°C

**Models:**

350 (Size 2-1/2" - 12")  
375 (Size 2-1/2" - 10")  
450 (Size 2-1/2" - 10")  
475 (Size 2-1/2" - 10")  
ZCSM-PF (Wireless Pressure and Flow Monitor, fits all sizes)  
ZCSM-RP (Wireless Pressure and Flow Monitor, fits all sizes)

Model 350 and 375 are certified for the following optional product suffixes in any combination:

(none) - includes iron flanged body with Model 48 AWWA C515 NRS Gate Valves (FXF)(GXF)  
L - shutoff valves not included with assembly  
OSY - shutoffs are model 48 AWWA C515 OSY gate valves (FXF)(GXF)(GXG)  
BGVIC - shutoffs are Victaulic butterfly valves (only used with grooved body) (GXG)  
DOM - shutoffs are domestic Clow gate valves (NRS or OSY (FXF)(GXG)(GXF))  
BG - shutoffs are Model 49 butterfly valves (only used with grooved body (GXG))  
BF - shutoffs are Model 49 butterfly valves (only used with grooved body (GXF))  
A - includes iron grooved body with Model 48 AWWA C515 NRS Gate Valves (GXG)(GXF) (2-1/2" - 10")  
AR - includes iron grooved body with stainless steel retrofit spool (2-1/2" - 10")  
AST - includes stainless steel grooved body (2-1/2" - 10")  
ASTR- includes stainless steel grooved body with stainless steel retrofit spool (2-1/2" - 10")  
DA - includes detector assembly (bypass)  
-509 - with AWWA C509 Gate Valves  
W1 - with wireless relief valve and pressure monitor



Product certified to NSF/ANSI/CAN 372 conforms to the requirements for "Lead Free" plumbing products as defined by California, Vermont, Maryland and Louisiana state laws and by section 1417 of the US SDWA.



Model 450 and 475 are certified for the following optional product suffixes in any combination:

- (none) - includes iron grooved body with Model 48 AWWA C515 NRS Gate Valves (GXG)(GXF)
- L - shutoff valves not included with assembly
- OSY - shutoffs are model 48 AWWA C515 OSY gate valves (GXF)(GXG)
- BGVIC - shutoffs are Victaulic butterfly valves (GXG)
- DOM - shutoffs are domestic Clow gate valves (NRS or OSY (GXF)(GXG))
- BG - shutoffs are Model 49 butterfly valves (GXG)
- BF - shutoffs are Model 49 butterfly valves (GXF)
- DA - includes detector assembly (bypass)
- 509 - with AWWA C509 Gate Valves
- ST - includes stainless steel body (4"-10")
- R - includes stainless steel retrofit spool (4"-10")
- V - vertical up orientation



Product certified to NSF/ANSI/CAN 372 conforms to the requirements for "Lead Free" plumbing products as defined by California, Vermont, Maryland and Louisiana state laws and by section 1417 of the US SDWA.