



Certified Product Listing

For:

Drinking Water System Components – Health Effects

Company:

Zurn Water, LLC - Wilkins
1747 Commerce Way
Paso Robles, CA 93446, United States

Plant Location:

Paso Robles, CA, United States

Standards:

NSF/ANSI/CAN 61 - 2022
NSF/ANSI 372 - 2022

Certificate:

Issued Date: 07/07/2020

Material/Product:

Reduced Pressure Principle Backflow Preventer (375, 475)
Double Check Valve Backflow Preventer (350, 450)

Contact Temperature:

23 ± 2°C

Models:

350 (Size 2-1/2" - 12")
375 (Size 2-1/2" - 10")
450 (Size 2-1/2" - 10")
475 (Size 2-1/2" - 10")
ZCSM-PF (Wireless Pressure and Flow Monitor, fits all sizes)
ZCSM-RP (Wireless Pressure and Flow Monitor, fits all sizes)

Model 350 and 375 are certified for the following optional product suffixes in any combination:

(none) - includes iron flanged body with Model 48 AWWA C515 NRS Gate Valves (FXF)(GXF)
L - shutoff valves not included with assembly
OSY - shutoffs are model 48 AWWA C515 OSY gate valves (FXF)(GXF)(GXG)
BGVIC - shutoffs are Victaulic butterfly valves (only used with grooved body) (GXG)
DOM - shutoffs are domestic Clow gate valves (NRS or OSY (FXF)(GXG)(GXF))
BG - shutoffs are Model 49 butterfly valves (only used with grooved body (GXG))
BF - shutoffs are Model 49 butterfly valves (only used with grooved body (GXF))
A - includes iron grooved body with Model 48 AWWA C515 NRS Gate Valves (GXG)(GXF) (2-1/2" - 10")
AR - includes iron grooved body with stainless steel retrofit spool (2-1/2" - 10")
AST - includes stainless steel grooved body (2-1/2" - 10")
ASTR- includes stainless steel grooved body with stainless steel retrofit spool (2-1/2" - 10")
DA - includes detector assembly (bypass)
-509 - with AWWA C509 Gate Valves
W1 - with wireless relief valve and pressure monitor



Product certified to NSF/ANSI/CAN 372 conforms to the requirements for "Lead Free" plumbing products as defined by California, Vermont, Maryland and Louisiana state laws and by section 1417 of the US SDWA.



ALS Group USA, Corp.

10450 Stancliff Rd. Suite 210 Houston, Texas 77099

Model 450 and 475 are certified for the following optional product suffixes in any combination:

(none) - includes iron grooved body with Model 48 AWWA C515 NRS Gate Valves (GXG)(GXF)
L - shutoff valves not included with assembly
OSY - shutoffs are model 48 AWWA C515 OSY gate valves (GXF)(GXG)
BGVIC - shutoffs are Victaulic butterfly valves (GXG)
DOM - shutoffs are domestic Clow gate valves (NRS or OSY (GXF)(GXG))
BG - shutoffs are Model 49 butterfly valves (GXG)
BF - shutoffs are Model 49 butterfly valves (GXF)
DA - includes detector assembly (bypass)
-509 - with AWWA C509 Gate Valves
ST - includes stainless steel body (4"-10")
R - includes stainless steel retrofit spool (4"-10")
V - vertical up orientation

ALS



Product certified to NSF/ANSI/CAN 372 conforms to the requirements for "Lead Free" plumbing products as defined by California, Vermont, Maryland and Louisiana state laws and by section 1417 of the US SDWA.

ALS Group's Product Certification Listing directory contains the most current certified product(s) and supersedes all printed copies of the listings.