



## Certified Product Listing

**For:**

Drinking Water System Components - Health Effects

**Company:**

Zurn Wilkins  
1747 Commerce Way  
Paso Robles, CA 93446, United States

**Plant Location:**

Paso Robles, CA, United States

**Standards:**

NSF/ANSI/CAN 61 - 2020  
NSF/ANSI/CAN 372 - 2020

**Certificate:**

Issued Date: 01/06/2020

**Material/Product:**

Automatic Control Valve (ZW 200 Series)

**Contact Temperature:**

23 ± 2°C

**Models:**

ZW204 (Size 1-1/4" - 16")  
ZW204A (Size 1-1/4" - 10")  
ZW204R (Size 3" - 10")  
ZW205 (Size 1-1/4" - 16")  
ZW205A (Size 1-1/4" - 10")  
ZW205R (Size 3" - 10")  
ZW206 (Size 1-1/4" - 16")  
ZW206A (Size 1-1/4" - 10")  
ZW206R (Size 3" - 10")  
ZW207 (Size 1-1/4" - 16")  
ZW207A (Size 1-1/4" - 10")  
ZW207R (Size 3" - 10")  
ZW209 (Size 1-1/4" - 16")  
ZW209A (Size 1-1/4" - 10")  
ZW209BP (Size 1-1/4" - 16")  
ZW209BPA (Size 1-1/4" - 10")  
ZW209BPR (Size 3" - 10")  
ZW209E (Size 1-1/4" - 16")  
ZW209EA (Size 1-1/4" - 10")  
ZW209ER (Size 3" - 10")  
ZW209H (Size 1-1/4" - 16")  
ZW209HA (Size 1-1/4" - 10")  
ZW209HR (Size 3" - 10")  
ZW209Q (Size 1-1/4" - 16")  
ZW209QA (Size 1-1/4" - 10")  
ZW209QR (Size 3" - 10")  
ZW209R (Size 3" - 10")



Product certified to NSF/ANSI/CAN 372 conforms to the requirements for "Lead Free" plumbing products as defined by California, Vermont, Maryland and Louisiana state laws and by section 1417 of the US SDWA.



# ALS Group USA, Corp.

3337 Michelson Drive, Suite CN750, Irvine, CA 92612

ZW218 (Size 1-1/4" - 16")  
ZW218A (Size 1-1/4" - 10")  
ZW218R (Size 3" - 10")  
ZW221 (Size 1-1/4" - 16")  
ZW221A (Size 1-1/4" - 10")  
ZW221D (Size 1-1/4" - 16")  
ZW221DA (Size 1-1/4" - 10")  
ZW221DR (Size 3" - 10")  
ZW221E (Size 1-1/4" - 16")  
ZW221EA (Size 1-1/4" - 10")  
ZW221ER (Size 3" - 10")  
ZW221R (Size 3" - 10")  
ZW222 (Size 1-1/4" - 16")  
ZW222A (Size 1-1/4" - 10")  
ZW222D (Size 1-1/4" - 16")  
ZW222DA (Size 1-1/4" - 10")  
ZW222DR (Size 3" - 10")  
ZW222R (Size 3" - 10")

## OPTIONS - All ACV Model Series:

### Body

None - Full port globe style  
A - Full port angle style  
R - Reduced Port globe style

### Function

E - Solenoid shut-off valve  
H - Pressure sustaining function  
Q - Downstream surge protection  
M - Modulating function  
C - Single check valve with isolation valve  
L - Closing speed control  
O - Opening speed control  
D - Dual set point (221/222 only)

### Pilot System

ST - Stainless steel tubing/ fittings  
SP - Stainless steel pilot assembly  
GL - Liquid filled gauge  
RV - Pilot installed on reverse side  
HP - High pressure  
LP - Low pressure  
BH - Braided hose tubing  
L1 - 5-55 ft level adjustment  
L2 - 45-85 ft level adjustment  
L3 - 75-230 ft level adjustment  
L4 - 220-345 ft level adjustment

### Connections

None - ANSI class 150 flanges  
G - IPS grooved  
TH - NPT threaded  
Y - ANSI class 300 flanges

### Main valve options

BP - Low flow bypass  
Z - ZPI visual position indicator

## Options specific to the different series:

### Series ZW204 Float Valve:

- Certified with PV-FNM Float Pilot



Product certified to NSF/ANSI/CAN 372 conforms to the requirements for "Lead Free" plumbing products as defined by California, Vermont, Maryland and Louisiana state laws and by section 1417 of the US SDWA.

ALS Group's Product Certification Listing directory contains the most current certified product(s) and supersedes all printed copies of the listings.



# ALS Group USA, Corp.

3337 Michelson Drive, Suite CN750, Irvine, CA 92612

Series ZW205 Pressure Relief/Sustaining Valve:

- Certified with PV-RLF or PV-RLFST Pilot

Series ZW206 Solenoid Control Valve:

- Certified for all solenoid options (PV-SOL3 and PV-SOL3SS)

- Certified with PV-ACL or PV-ACLST Pilot and NR3XL, PRXL, PRST, PV-PRD, or PV-PRDST Pilot

Series ZW207 Excess Pressure Shutdown Valve:

- Certified with PV-RLF or PV-RLFST Pilot

Series ZW209 Pressure Reducing Valve:

- Certified with NR3XL, PRXL, PRST, PV-PRD, or PV-PRDST Pilot

Series ZW209BP Pressure Reducing Valve with Low Flow By-Pass:

- Certified with NR3XL, PRXL, PRST, PV-PRD, or PV-PRDST Pilot

Series ZW209E Pressure Reducing Valve with Solenoid Shut-Off Valve:

- Certified with all Solenoid Options (PV-SOL3 and PV-SOL3SS)

- Certified with PV-ACL or PV-ACLST Pilot and NR3XL, PRXL, PRST, PV-PRD, or PV-PRDST Pilot

Series ZW209H Pressure Reducing/Sustaining Valve:

- Certified with PV-RLF or PV-RLFST Pilot

Series ZW209Q Pressure Reducing/Sustaining Valve:

- Certified with PV-RLF or PV-RLFST and NR3XL, PRXL, PRST, PV-PRD, or PV-PRDST Pilot

Series ZW221 Altitude Control Valve (One-Way Single Set Point):

- Certified with PV-ACL or PV-ACLST and PV-ALT or PV-ALTST Pilot

Series ZW222 Altitude Control Valve (Two-Way Single Set Point):

- Certified with PV-ACL or PV-ACLST and PV-ALT or PV-ALTST Pilot

Series ZW221D Altitude Control Valve (One-Way Dual Set Point):

- Certified with PV-ACL or PV-ACLST and PV-ALT-D or PV-ALTST-D Pilot

Series ZW222D Altitude Control Valve (Two-Way Dual Set Point):

- Certified with PV-ACL or PV-ACLST and PV-ALT-D or PV-ALTST-D Pilot



Product certified to NSF/ANSI/CAN 372 conforms to the requirements for "Lead Free" plumbing products as defined by California, Vermont, Maryland and Louisiana state laws and by section 1417 of the US SDWA.