



Certified Product Listing

For:

Drinking Water System Components – Health Effects

Company:

Zurn Water, LLC - Wilkins
1747 Commerce Way
Paso Robles, CA 93446, United States

Plant Location:

Paso Robles, CA, United States

Standards:

NSF/ANSI/CAN 61 - 2022
NSF/ANSI 372 - 2022

Certificate:

Issued Date: 12/23/2022

Material/Product:

Automatic Control Valve (ZW 200 Series)

Contact Temperature:

60 ± 2°C

Models:

ZW204 (Size 1-1/4" - 16")
ZW204A (Size 1-1/4" - 10")
ZW204R (Size 3" - 10")
ZW205 (Size 1-1/4" - 16")
ZW205A (Size 1-1/4" - 10")
ZW205R (Size 3" - 10")
ZW206 (Size 1-1/4" - 16")
ZW206A (Size 1-1/4" - 10")
ZW206R (Size 3" - 10")
ZW207 (Size 1-1/4" - 16")
ZW207A (Size 1-1/4" - 10")
ZW207R (Size 3" - 10")
ZW209 (Size 1-1/4" - 16")
ZW209A (Size 1-1/4" - 10")
ZW209BP (Size 1-1/4" - 16")
ZW209BPA (Size 1-1/4" - 10")
ZW209BPR (Size 3" - 10")
ZW209E (Size 1-1/4" - 16")
ZW209EA (Size 1-1/4" - 10")
ZW209ER (Size 3" - 10")
ZW209H (Size 1-1/4" - 16")
ZW209HA (Size 1-1/4" - 10")
ZW209HR (Size 3" - 10")
ZW209Q (Size 1-1/4" - 16")
ZW209QA (Size 1-1/4" - 10")
ZW209QR (Size 3" - 10")
ZW209R (Size 3" - 10")



Product certified to NSF/ANSI/CAN 372 conforms to the requirements for "Lead Free" plumbing products as defined by California, Vermont, Maryland and Louisiana state laws and by section 1417 of the US SDWA.



ALS Group USA, Corp.

10450 Stancliff Rd. Suite 210 Houston, Texas 77099

ZW218 (Size 1-1/4" - 16")
ZW218A (Size 1-1/4" - 10")
ZW218R (Size 3" - 10")
ZW221 (Size 1-1/4" - 16")
ZW221A (Size 1-1/4" - 10")
ZW221D (Size 1-1/4" - 16")
ZW221DA (Size 1-1/4" - 10")
ZW221DR (Size 3" - 10")
ZW221E (Size 1-1/4" - 16")
ZW221EA (Size 1-1/4" - 10")
ZW221ER (Size 3" - 10")
ZW221R (Size 3" - 10")
ZW222 (Size 1-1/4" - 16")
ZW222A (Size 1-1/4" - 10")
ZW222D (Size 1-1/4" - 16")
ZW222DA (Size 1-1/4" - 10")
ZW222DR (Size 3" - 10")
ZW222R (Size 3" - 10")

OPTIONS - All ACV Model Series:

Body

None = Full port globe style
A = Full port angle style
R = Reduced Port globe style

Function

E = Solenoid shut-off valve
H = Pressure sustaining function
Q = Downstream surge protection
M = Modulating function
C = Single check valve with isolation valve
L = Closing speed control
O = Opening speed control
D = Dual set point (221/222 only)

Pilot System

ST = Stainless steel tubing/ fittings
SP = Stainless steel pilot assembly
GL = Liquid filled gauge
RV = Pilot installed on reverse side
HP = High pressure
LP = Low pressure
BH = Braided hose tubing
L1 - 5-55 ft level adjustment
L2 - 45-85 ft level adjustment
L3 - 75-230 ft level adjustment
L4 - 220-345 ft level adjustment

Connections

None = ANSI class 150 flanges
G = IPS grooved
TH = NPT threaded
Y = ANSI class 300 flanges

Main valve options

BP = Low flow bypass
Z = ZPI visual position indicator

Options specific to the different series:

Series ZW204 Float Valve:

- Certified with PV-FNM Float Pilot



Product certified to NSF/ANSI/CAN 372 conforms to the requirements for "Lead Free" plumbing products as defined by California, Vermont, Maryland and Louisiana state laws and by section 1417 of the US SDWA.

ALS Group's Product Certification Listing directory contains the most current certified product(s) and supersedes all printed copies of the listings.



ALS Group USA, Corp.

10450 Stancliff Rd. Suite 210 Houston, Texas 77099

Series ZW205 Pressure Relief/Sustaining Valve:

- Certified with PV-RLF or PV-RLFST Pilot

Series ZW206 Solenoid Control Valve:

- Certified for all solenoid options (PV-SOL3 and PV-SOL3SS)

- Certified with PV-ACL or PV-ACLST Pilot and NR3XL, PRXL, PRST, PV-PRD, or PV-PRDST Pilot

Series ZW207 Excess Pressure Shutdown Valve:

- Certified with PV-RLF or PV-RLFST Pilot

Series ZW209 Pressure Reducing Valve:

- Certified with NR3XL, PRXL, PRST, PV-PRD, or PV-PRDST Pilot

Series ZW209BP Pressure Reducing Valve with Low Flow By-Pass:

- Certified with NR3XL, PRXL, PRST, PV-PRD, or PV-PRDST Pilot

Series ZW209E Pressure Reducing Valve with Solenoid Shut-Off Valve:

- Certified with all Solenoid Options (PV-SOL3 and PV-SOL3SS)

- Certified with PV-ACL or PV-ACLST Pilot and NR3XL, PRXL, PRST, PV-PRD, or PV-PRDST Pilot

Series ZW209H Pressure Reducing/Sustaining Valve:

- Certified with PV-RLF or PV-RLFST Pilot

Series ZW209Q Pressure Reducing/Sustaining Valve:

- Certified with PV-RLF or PV-RLFST and NR3XL, PRXL, PRST, PV-PRD, or PV-PRDST Pilot

Series ZW221 Altitude Control Valve (One-Way Single Set Point):

- Certified with PV-ACL or PV-ACLST and PV-ALT or PV-ALTST Pilot

Series ZW222 Altitude Control Valve (Two-Way Single Set Point):

- Certified with PV-ACL or PV-ACLST and PV-ALT or PV-ALTST Pilot

Series ZW221D Altitude Control Valve (One-Way Dual Set Point):

- Certified with PV-ACL or PV-ACLST and PV-ALT-D or PV-ALTST-D Pilot

Series ZW222D Altitude Control Valve (Two-Way Dual Set Point):

- Certified with PV-ACL or PV-ACLST and PV-ALT-D or PV-ALTST-D Pilot

ALS



Product certified to NSF/ANSI/CAN 372 conforms to the requirements for "Lead Free" plumbing products as defined by California, Vermont, Maryland and Louisiana state laws and by section 1417 of the US SDWA.

ALS Group's Product Certification Listing directory contains the most current certified product(s) and supersedes all printed copies of the listings.