



## Certified Product Listing

**For:**

Drinking Water System Components – Health Effects

**Company:**

VAG USA LLC  
9025 Marshall Rd.  
Cranberry Twp., PA 16066, United States

**Plant Location:**

Paso Robles, CA, United States

**Standards:**

NSF/ANSI/CAN 61 - 2022  
NSF/ANSI/CAN 372 - 2022

**Certificate:**

Issued Date: 11/09/2016

**Material/Product:**

Automatic Control Valves

**Contact Temperature:**

23 ± 2°C

**Models:**

5273 (Size 1-1/4" - 16")  
5273-A (Size 1-1/4" - 10")  
5273R (Size 3" - 10")  
5320 (Size 1-1/4" - 16")  
5320-A (Size 1-1/4" - 10")  
5320-A-DL (Size 1-1/4" - 10")  
5320-DL (Size 1-1/4" - 16")  
5320R (Size 3" - 10")  
5320R-A-DL (Size 3" - 10")  
5325 (Size 1-1/4" - 16")  
5325-A (Size 1-1/4" - 10")  
5325R (Size 3" - 10")  
5330 (Size 1-1/4" - 16")  
5330-A (Size 1-1/4" - 10")  
5330-A-DL (Size 1-1/4" - 10")  
5330-DL (Size 1-1/4" - 16")  
5330R (Size 3" - 10")  
5330R-DL (Size 3" - 10")  
5450 (Size 1-1/4" - 16")  
5450-A (Size 1-1/4" - 10")  
5450B (Size 1-1/4" - 16")  
5450B-A (Size 1-1/4" - 10")  
5450BR (Size 3" - 10")  
5450R (Size 3" - 10")  
5455 (Size 1-1/4" - 16")  
5455-A (Size 1-1/4" - 10")  
5455R (Size 3" - 10")



Product certified to NSF/ANSI/CAN 372 conforms to the requirements for "Lead Free" plumbing products as defined by California, Vermont, Maryland and Louisiana state laws and by section 1417 of the US SDWA.



# ALS Group USA, Corp.

3337 Michelson Drive, Suite CN750, Irvine, CA 92612

5470 (Size 1-1/4" - 16")  
5470-A (Size 1-1/4" - 10")  
5470R (Size 3" - 10")  
5560 (Size 1-1/4" - 16")  
5560-A (Size 1-1/4" - 10")  
5560R (Size 3" - 10")  
5670 (Size 1-1/4" - 16")  
5670-A (Size 1-1/4" - 10")  
5670R (Size 3" - 10")  
5700 (Size 1-1/4" - 16")  
5700-A (Size 1-1/4" - 10")  
5700R (Size 3" - 10")

## OPTIONS - All ACV Model Series:

### Body

- G " Full port globe style
- A " Full port angle style
- R " Reduced Port globe style

### Function

- xxx5 " Solenoid shut-off valve
- xx7x " Pressure sustaining function
- CX " Single check valve with isolation valve
- CL " Closing speed control
- OP " Opening speed control
- DL " Dual set point (221/222 only)

### Pilot System

- S9 " Stainless steel tubing/ fittings
- SP " Stainless steel pilot assembly
- LG " Liquid filled gauge
- LH " Pilot installed on reverse side
- DH, -LC " High pressure range pilot
- DM, -LB - Standard pressure range pilot
- DL, -L3, -L2, -LA " Low pressure range pilot
- W1 - 5-55 ft level adjustment
- W2 - 45-85 ft level adjustment
- W3 - 75-230 ft level adjustment
- W4 - 220-345 ft level adjustment

### Connections

- 15 " ANSI class 150 flanges
- 00 " NPT threaded
- 30 " ANSI class 300 flanges

### Main valve options

- B " Low flow bypass
- PI " ZPI visual position indicator

## Options specific to the different series:

### Series 5560 Float Valve:

- Certified with GA-FNM Float Pilot

### Series 5670 Pressure Relief/Sustaining Valve:

- Certified with GA-RLF or GA-RLFST Pilot

### Series 5700 Solenoid Control Valve:

- Certified for all solenoid options (GA-SOL3 and GA-SOL3SS)
- Certified with GA-ACL or GA-ACLST Pilot and GA-NR3XL, GA-PRXL, GA-PRST, GA-PRD, or GA-PRDST Pilot

### Series 5450 Pressure Reducing Valve:

- Certified with GA-NR3XL, GA-PRXL, GA-PRST, GA-PRD, or GA-PRDST Pilot

### Series 5450B Pressure Reducing Valve with Low Flow By-Pass:

- Certified with GA-NR3XL, GA-PRXL, GA-PRST, GA-PRD, or GA-PRDST Pilot

### Series 5455 Pressure Reducing Valve with Solenoid Shut-Off Valve:



Product certified to NSF/ANSI/CAN 372 conforms to the requirements for "Lead Free" plumbing products as defined by California, Vermont, Maryland and Louisiana state laws and by section 1417 of the US SDWA.



# ALS Group USA, Corp.

3337 Michelson Drive, Suite CN750, Irvine, CA 92612

- Certified with all Solenoid Options (GA-SOL3 and GA-SOL3SS)
  - Certified with GA-ACL or GA-ACLST Pilot and GA-NR3XL, GA-PRXL, GA-PRST, GA-PRD, or GA-PRDST Pilot
- Series 5470 Pressure Reducing/Sustaining Valve:
- Certified with GA-RLF or GA-RLFST Pilot
- Series 5320 Altitude Control Valve (One-Way Single Set Point):
- Certified with GA-ACL or GA-ACLST and GA-ALT or GA-ALTST Pilot
- Series 5330 Altitude Control Valve (Two-Way Single Set Point):
- Certified with GA-ACL or GA-ACLST and GA-ALT or GA-ALTST Pilot
- Series 5320-DL Altitude Control Valve (One-Way Dual Set Point):
- Certified with GA-ACL or GA-ACLST and GA-ALT-D or GA-ALTST-D Pilot
- Series 5330-DL Altitude Control Valve (Two-Way Dual Set Point):
- Certified with GA-ACL or GA-ACLST and GA-ALT-D or GA-ALTST-D Pilot



Product certified to NSF/ANSI/CAN 372 conforms to the requirements for "Lead Free" plumbing products as defined by California, Vermont, Maryland and Louisiana state laws and by section 1417 of the US SDWA.