



Certified Product Listing

For:

Drinking Water System Components – Health Effects

Company:

Aquafix Resins Inc
1700 Talbot Blvd, 3rd floor
Chicoutimi, Quebec G7H7Y1, Canada

Plant Location:

Quebec, Canada

Standards:

NSF/ANSI/CAN 61 - 2022

Certificate:

Issued Date: 04/27/2017

Material/Product:

Structural Polymeric Coating

Contact Temperature:

77 ± 5°F

Models:

Acuro IC-202



Product certified to NSF/ANSI/CAN 372 conforms to the requirements for "Lead Free" plumbing products as defined by California, Vermont, Maryland and Louisiana state laws and by section 1417 of the US SDWA.



Material Characteristics:

Minimum pipe diameter (inches): 6

Maximum pipe surface area/volume ratio (sq in/L): 40.7

Maximum dry film thickness per coat (mils): 240

Is additional coating required (e.g. top coat, primer, intermediate coat)? (Y/N): No

Total cure time and temperature: 24 hours at 77 Â°F

Shortest cure time between coats or layers: 7 seconds, tack free at 30 seconds

Mix ratio: 1:1 by Volume

Colors: Original

Is this paint/coating system intended to be applied to a pipe? (Y/N): Yes

(1) Certified for use on a new pipe? (Y/N): No

(2) Certified for use on a pipe intended for immediate return to service? (Y/N): Yes

Additional comments:

Flushing or preparation instruction prior to use: AWWA standard (slug method) using 200 ppm CL2

a) Flushing time: 15 minutes

b) Estimate Flow Rate (gpm): 3 gpm

c) Temperature of Flush: 77 Â± 5 Â°C



Product certified to NSF/ANSI/CAN 372 conforms to the requirements for "Lead Free" plumbing products as defined by California, Vermont, Maryland and Louisiana state laws and by section 1417 of the US SDWA.