



## Certified Product Listing

**For:**

Drinking Water System Components - Health Effects

**Company:**

Resin Acuro  
156 Fairhaven Street  
Hudson, Quebec JOP1HO, Canada

**Plant Location:**

Quebec, Canada

**Standards:**

NSF/ANSI/CAN 61 - 2020

**Certificate:**

Issued Date: 07/13/2020

**Material/Product:**

Polymeric Resin

**Contact Temperature:**

23 ± 2°C

**Models:**

Tomahawk BluKote



Product certified to NSF/ANSI 372 conforms to the requirements for "Lead Free" plumbing products as defined by California, Vermont, Maryland and Louisiana state laws and by section 1417 of the US SDWA.



## Material Characteristics:

Minimum pipe diameter (inches): 0.5

Maximum pipe surface area/volume ratio (sq in/L): 488

Maximum dry film thickness per coat (mils): 80

Is additional coating required (e.g. top coat, primer, intermediate coat)? (Y/N): Refer to manufacturer instructions for details

Total cure time and temperature: 48 hours

Final cure time: 48 hours

Mix ratio: 3:1 per volume

Is this paint/coating system intended to be applied to a pipe? (Y/N): Yes

(1) Certified for use on a new pipe? (Y/N): Yes

(2) Certified for use on a pipe intended for immediate return to service? (Y/N): Yes



Product certified to NSF/ANSI 372 conforms to the requirements for "Lead Free" plumbing products as defined by California, Vermont, Maryland and Louisiana state laws and by section 1417 of the US SDWA.