

ALS Group USA, Corp.

10450 Stancliff Rd. Suite 210 Houston, Texas 77099

Certified Product Listing

For:

Drinking Water System Components - Health Effects

Company:

Tank Connection LLC 3609 N. 16th Street, Parsons, KS 67357, United States

Plant Location:

Parsons, KS, USA

Standards:

NSF/ANSI/CAN 61 - 2022

Certificate:

Issued Date: 02/10/2022

Material/Product:

Bolted RTP Water tanks

Contact Temperature:

23 ± 2°C

Models:

H-Style #50 AZ63 Anode RTP Bolted Steel Tank

Note:

- 1. The H-style#50 AZ63 Anodes are certified for use with tank connection certified RTP Bolted steel tanks only.
- 2. The AZZ Incorporated Hot Dip Galvanized Coating is certified for use with tank >= 20,000 gallons.
- 3. The certified RTP Bolted steel tank is certified for use with uncoated 304/304L stainless steel tanks >= 4,035 gallons, uncoated 316/316L stainless steel tanks >= 4,035 gallons, uncoated 304/304L stainless steel pipes >= 3/4" nominal diameter, uncoated 316/316L stainless steel pipes >= 3/4" nominal diameter, uncoated EverTUFF Industrial PVC pipes, and uncoated Charlotte Pipe PVC pipes.
- 4. Aluminum Geodesic Domes and/or covers are non-wetted components and are installed above the liquid product zone in conformance with requirements.







10450 Stancliff Rd. Suite 210 Houston, Texas 77099

Material Characteristics:

Minimum tank size (gallons): 4035

Is additional coating required (e.g. top coat, primer, intermediate coat)? (Y/N): No

Final cure time: 24 hours

Is this paint/coating system intended to be applied to a pipe? (Y/N): Yes

(1) Certified for use on a new pipe? (Y/N): No

(2) Certified for use on a pipe intended for immediate return to service? (Y/N): No

Additional comments:

- 1. The H-style#50 AZ63 Anodes are certified for use with tank connection certified RTP Bolted steel tanks only.
- 2. The AZZ Incorporated Hot Dip Galvanized Coating is certified for use with tank >= 20,000 gallons.
- 3. The certified RTP Bolted steel tank is certified for use with uncoated 304/304L stainless steel tanks >= 4,035 gallons, uncoated 316/316L stainless steel tanks >= 4,035 gallons, uncoated 304/304L stainless steel pipes >= 3/4" nominal diameter, uncoated 316/316L stainless steel pipes >= 3/4" nominal diameter, uncoated EverTUFF Industrial PVC pipes, and uncoated Charlotte Pipe PVC pipes.



