



ALS Group USA, Corp.

10450 Stancliff Rd. Suite 210 Houston, Texas 77099

Certified Product Listing

For:

Drinking Water System Components – Health Effects

Company:

Nu Flow Technologies (2000) Inc.
1270 W Mission Avenue
Escondido, California 92029, United States

Plant Location:

Eaglescliffe, Stockton-on-Tees, UK

Standards:

NSF/ANSI/CAN 61 - 2022

Certificate:

Issued Date: 11/20/2024

Material/Product:

In-Situ polymeric Lining

Contact Temperature:

23 ± 2°C

Models:

Serline 266L



Product certified to NSF/ANSI/CAN 372 conforms to the requirements for "Lead Free" plumbing products as defined by California, Vermont, Maryland and Louisiana state laws and by section 1417 of the US SDWA.



Material Characteristics:

Minimum pipe diameter (inches): 0.5 inch

Maximum dry film thickness per coat (mils): 80 Mils

Is additional coating required (e.g. top coat, primer, intermediate coat)? (Y/N): No

Total cure time and temperature: 2 hours / a minimum 7 degree Celsius

Final cure time: 2 Hours

Colors: Pale Blue

Is this paint/coating system intended to be applied to a pipe? (Y/N): Yes

(1) Certified for use on a new pipe? (Y/N): No

(2) Certified for use on a pipe intended for immediate return to service? (Y/N): Yes

Additional comments:

Maximum Pipe Diameter - 3.0 inch



Product certified to NSF/ANSI/CAN 372 conforms to the requirements for "Lead Free" plumbing products as defined by California, Vermont, Maryland and Louisiana state laws and by section 1417 of the US SDWA.