



# ALS Group USA, Corp.

10450 Stancliff Rd. Suite 210 Houston, Texas 77099

## Certified Product Listing

**For:**

Drinking Water System Components – Health Effects

**Company:**

BASF Corporation  
1609 Biddle Avenue  
Wyandotte, MI 48192, United States

**Plant Location:**

Geismar, LA, USA

**Standards:**

NSF/ANSI/CAN 61 - 2024  
NSF/ANSI 372 - 2024

**Certificate:**

Issued Date: 07/22/2025

**Material/Product:**

Spray Coating

**Contact Temperature:**

23 ± 2°C

**Models:**

Elastocast S 55090R Resin/Elastocast S 55090T Isocyanate  
Elastocast S 55095R Resin/Elastocast S 55090T Isocyanate  
Elastocoat 95540R BLK Resin/Elastocoat 95540T Isocyanate  
Elastocoat 95540R GRY Resin/Elastocoat 95540T Isocyanate  
Elastocoat 95540R NAT Resin/Elastocoat 95540T Isocyanate  
Elastocoat 95540R TAN Resin/Elastocoat 95540T Isocyanate



Product certified to NSF/ANSI/CAN 372 conforms to the requirements for "Lead Free" plumbing products as defined by California, Vermont, Maryland and Louisiana state laws and by section 1417 of the US SDWA.



## Material Characteristics:

Minimum pipe diameter (inches): 120

Minimum tank size (gallons): 100000

Maximum dry film thickness per coat (mils): 110 mil

Number of coats: 1

Is additional coating required (e.g. top coat, primer, intermediate coat)? (Y/N): No

Total cure time and temperature: 24 hours at 23C

Mix ratio: 1:1 by volume (A:B)

Colors: Black, Natural

Is this paint/coating system intended to be applied to a pipe? (Y/N): Yes

(1) Certified for use on a new pipe? (Y/N): Yes

(2) Certified for use on a pipe intended for immediate return to service? (Y/N): Yes



Product certified to NSF/ANSI/CAN 372 conforms to the requirements for "Lead Free" plumbing products as defined by California, Vermont, Maryland and Louisiana state laws and by section 1417 of the US SDWA.