



Certified Product Listing

For:

Drinking Water System Components – Health Effects

Company:

Zurn Water, LLC - Wilkins
1747 Commerce Way
Paso Robles, CA 93446, United States

Plant Location:

Paso Robles, CA, United States

Standards:

NSF/ANSI/CAN 61 - 2022
NSF/ANSI 372 - 2022

Certificate:

Issued Date: 01/16/2025

Material/Product:

Water Pressure Reducing Valves (500XL3, 600XL3, 625XL3)

Contact Temperature:

60 ± 2°C

Models:

500XL3 (Size 1" - 4")
600XL3 (1", 1-1/4", 1-1/2", 2")
625XL3 (1", 1-1/4", 1-1/2", 2")

Options: (Any combination of options may be used)

None - Standard with single union FNPT inlet x FNPT outlet

C - Single union Copper Sweat inlet x FNPT outlet
F - Flanged Body, ANSI Class 150 (2-1/2"-4")
G - Tapped and plugged with gauge
DU - Double union FNPT x FNPT
DUC - Double union Copper Sweat x Sweat
HR - High range, outlet adjust from 75psi to 125 psi
Y - With lead-free bronze "Y" strainer on inlet (1"- 3" 500XL3)
FY- With Ductile iron "Y" type flanged strainer (2-1/2" - 4" 500XL3)