



ALS Group USA, Corp.

10450 Stancliff Rd. Suite 210 Houston, Texas 77099

Certified Product Listing

For:

Drinking Water System Components – Health Effects

Company:

Henry Company
99 North Pacific Coast Highway, Suite 800
El Segundo , CA 90245, United States

Plant Location:

Foothill Ranch, CA, United States

Standards:

NSF/ANSI/CAN 61 - 2022

Certificate:

Issued Date: 07/21/2022

Material/Product:

Spray-Applied Polyurea Waterproofing Membrane

Contact Temperature:

23 ± 2°C

Models:

FX-650



Product certified to NSF/ANSI/CAN 372 conforms to the requirements for "Lead Free" plumbing products as defined by California, Vermont, Maryland and Louisiana state laws and by section 1417 of the US SDWA.

ALS Group's Product Certification Listing directory contains the most current certified product(s) and supersedes all printed copies of the listings.



Material Characteristics:

Minimum tank size (gallons): 100

Maximum tank surface area/volume ratio (sq in/L): 13.3

Is additional coating required (e.g. top coat, primer, intermediate coat)? (Y/N): No

Final cure time: 24 hours

Colors: Aqua Blue, Blue, Black, Gray, Tan

Is this paint/coating system intended to be applied to a pipe? (Y/N): No

ALS