



ALS Group USA, Corp.

10450 Stancliff Rd. Suite 210 Houston, Texas 77099

Certified Product Listing

For:

Drinking Water System Components – Health Effects

Company:

Resimac Limited
Unit B, Park Barn Estate, Station Road
Topcliffe, Thirsk YO7 3SE, United Kingdom

Plant Location:

Topcliffe, Thirsk North Yorkshire, United Kingdom

Standards:

NSF/ANSI/CAN 61 - 2022
NSF/ANSI 372 - 2022

Certificate:

Issued Date: 06/14/2024

Material/Product:

In-Situ Rapid Setting Polymeric Lining

Contact Temperature:

23 ± 2°C

Models:

Resiline 320



Product certified to NSF/ANSI/CAN 372 conforms to the requirements for "Lead Free" plumbing products as defined by California, Vermont, Maryland and Louisiana state laws and by section 1417 of the US SDWA.



Material Characteristics:

Minimum pipe diameter (inches): 4

Maximum pipe surface area/volume ratio (sq in/L): 61

Maximum dry film thickness per coat (mils): 14 mm

Is additional coating required (e.g. top coat, primer, intermediate coat)? (Y/N): No

Total cure time and temperature: 1 hour at 3Â°C

Shortest cure time between coats or layers: 90 seconds

Final cure time: 1 hour

Mix ratio: 1.52:1 vol

Colors: Blue

Is this paint/coating system intended to be applied to a pipe? (Y/N): Yes

(1) Certified for use on a new pipe? (Y/N): Yes

(2) Certified for use on a pipe intended for immediate return to service? (Y/N): Yes